

AL	'ALUM	INIUM	RATCHET	LEVER	HOISTS	AL
						1

Capacity (SWL) kgs	Falls of load chain	Load chain part no.	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs	Price £	Additional lifting height £/m
750	1	53012	1.5	315	6.4	£260	£13
1000	1	53012	1.5	325	6.6	£293	£13
1500	1	2107639	1.5	380	10.0	£368	£14
3000	1	2107649	1.5	455	18.0	£496	£19

Spare parts for Lever hoists are on pages 138-139.

The enclosed housing, handlever, and handwheel are made from high quality aluminium. Due to precise needle bearings, the hoist can be operated with little effort. Its low tare weight is an advantage when the hoist has to be carried over longer distances on different assignments. The chain guide is cast into the body to ensure faultless chain movement. The standard free chaining device serves to quickly attach the load or to pull the chain through the hoist in both directions. This universal ratchet lever hoist is "a must" in any service vehicle.

*ONLY 240mm

0000000

HANDY 'THE SMALLEST' RATCHET LEVER HOISTS

							100001001111
Capacity (SWL) kgs	Falls of load chain	Load chain part no.	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs	Price £	Additional lifting height £/m
250* 500	1	2100004 2100004	1.5 1.5	240 282	2.2 2.8	£79 £89	£9 £9

This hoist is the smallest and lightest ratchet lever hoist in the Yale range. Due to the multitude of application possibilities, e.g. industry, trade, and service. This ratchet lever hoist is indispensable. The extremely low tare weight and very compact design makes the hoist easy to use, even in very confined working conditions. The standard free chaining device serves to quickly attach the load or to pull the chain through the hoist in both directions.



The PT is probably the most universal ratchet lever hoist in the Yale range. The pressed steel housing provides an extremely low weight. The standard free chaining device serves to quickly attach the load or to pull the chain through the hoist in both directions. Low operating effort and low overall height are further outstanding features. The PT really is a good, versatile, all round ratchet lever hoist suitable for almost all standard applications.



UNO plus 'ECONOMY' RATCHET LEVER HOISTS

Capacity (SWL) kgs	Falls of load chain	Load chain part no.	Lifting height mtrs	Closed height mm	Weight @ std. HOL kgs	Price for standard unit £	Additional lifting height £/m
750 1500 3000	1 1 1	4307635 4307642 4307647	1.5 1.5 1.5	350 420 520	7.0 11.0 21.0	£105 £124 £182	£11 £14 £20
6000	2	4307647	1.5	700	28.0	£273	£40

The Yale UNOplus is a versatile ratchet lever hoist designed for pulling, lifting, and lashing of loads. Its features include a compact design, robust stamped steel construction, and a favourable price / efficiency ratio. The unit is also very lightweight and comes complete with a free chaining device as standard that serves to quickly attach the load or to pull the chain through the hoist in both directions.

The UNOPLUS ratchet lever hoist can also be supplied to ATEX APPROVED Spark Resistant specification. See page 13 for details.

